95 GHz CW Emitter VZB2788A1

DESCRIPTION

The model VZB2788A1 is a self contained 95 GHz Emitter consisting of an air-cooled Extended Interaction Klystron (EIK), power supply, cooling system, input and output RF components, and supporting electronics for control, monitoring and system protection contained in a wheeled cabinet. Remote operation is available through an interface to a laptop computer using the software provided. This equipment comes with a full complement of operating, control and protective equipment, and supporting documentation.

SPECIFICATIONS

Operating Frequency: $95.0 \text{ GHz} \pm 150 \text{ MHz}$

Output Power: 80 W CW

Harmonic Distortion: -20dBc maximum

Noise Figure: 35dB maximum

RF Output Connection: WR-10 with UG-387/U flange

Dimensions: 55" H x 23" W x 32" D

Weight: 240 kg.

Primary Power: 220 VAC, 50/60Hz, single

phase

Operating Temperature: +5° to +40° Celsius

FEATURES

- Front panel control or remote control via rear panel mounted, IEEE-488 bus.
- Internal forced air cooling permitting continuous full power operation.



Amplifier Protection:

Over-temperature RF output mismatch Waveguide arc

Front Panel Fault / Alarm Display:

High Reflected Power Waveguide Arc Tube Over-temperature **Excessive Duty Cycle**

Front Panel Gage / LCD or Controller Values:

Forward RF Power Reverse RF Power **Body Current** Cathode Voltage Beam Current Power Supply Temperature

RF Frequency

RF Attenuator Setting

Available accessories:

- Source oscillator with power and frequency adjustment
- High power rated bi-directional coupler
- Integrated dry air pump providing positive air flow within the waveguide.

CPI Canada has developed and manufactured millimetre wave klystrons for over 35 years. We specialize in pulsed and CW devices from 17 GHz to 220 GHz. Many of these pulsed or CW EIKs may be configured for use in high power threat emitter service or customized as required.

The values listed represent typical performance from testing.

Formal controlled specifications, with minimum and maximum values, for use in equipment design, may be obtained from CPI.

10880 Wilshire Blvd Los Angeles CA 90024 USA

Phone: +1.888.315.9545

Email: contact@orbitalconnect.com https://store.orbitalconnect.com

